

4bride (AHD/TVI/CVI/CVBS) Camera				
NO	Model	Specifications	Image	Price
1	HST-32D11E	1/2.7" 2MP(1920*1080) CMOS, 1080P@25fps(PAL);1080P@30fps (NTSC) Single SMT LED ,IR distance:10-20m ,3D DNR, DWDR ,Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 2.8mm lens ,Video Linkage with Access Control System(BioSecurity 3.0)		call us
2	HST-32D12B	1/2.7" 2MP(1920*1080) CMOS, 1080P@25fps(PAL);1080P@30fps (NTSC) Single SMT LED ,IR distance:10-20m ,3D DNR, DWDR ,Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 3.6mm lens ,Video Linkage with Access Control System(BioSecurity 3.0)		call us
3	HST-32D13B	1/2.7" 2MP(1920*1080) CMOS, 1080P@25fps(PAL);1080P@30fps (NTSC) Single SMT LED ,IR distance:10-20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 6mm lens , Video Linkage with Access Control System(BioSecurity 3.0)		call us
4	HST-32E11E	1/2.9" 2MP(1920*1080) CMOS, 1080P@25fps(PAL);1080P@30fps (NTSC) Single SMT LED ,IR distance:10-20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 2.8mm lens , Video Linkage with Access Control System(BioSecurity 3.0)		call us

5	HST-32E12B	<p>1/2.9" 2MP(1920*1080) CMOS, 1080P@25fps(PAL);1080P@30fps(NTSC) Single SMT LED ,IR distance:10-20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 3.6mm lens , Video Linkage with Access Control System(BioSecurity 3.0)</p>		call us
6	HST-32E13B	<p>1/2.9"2MP(1920*1080)CMOS, 1080P@25fps(PAL);1080P@30fps(NTSC) Single SMT LED ,IR distance:10 -20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/TVI/CVI/CVBS video output , IP67 ingress protection , 6mm lens , Video Linkage with Access Control System(BioSecurity 3.0)</p>		call us
7	HST-34F11E	<p>1/3"4MP(2560*1440) CMOS, 4MP@25fps(PAL);4MP@30fps (NTSC) Single SMT LED ,IR distance:10 -20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/CVI/CVBS video output , IP67 ingress protection , 2.8mm lens , Video Linkage with Access Control System(BioSecurity 3.0)</p>		call us
8	HST-34F12B	<p>1/3" 4MP(2560*1440) CMOS, 4MP@25fps(PAL); 4MP@30fps(NTSC) Single SMT LED ,IR distance:10 -20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/CVI/CVBS video output , IP67 ingress protection , 3.6mm lens , Video Linkage with Access Control System(BioSecurity 3.0)</p>		call us
9	HST-34F13B	<p>1/3" 4MP(2560*1440) CMOS, 4MP@25fps(PAL); 4MP@30fps(NTSC) Single SMT LED ,IR distance:10 -20m ,3D DNR, DWDR , Lightning Protection up to 6KV ,AHD/CVI/CVBS video output , IP67 ingress protection , 6mm lens , Video Linkage with Access Control System(BioSecurity 3.0)</p>		call us

5brid (AHD/TVI/CVI/CVBS/IP) C-Project DVRs

10	HST-ET04	<p>4ch video , 4ch audio , 1 IPC (ONVIF Profile S) , 1 SATA OS : Embedded Linux - Built in flash memory , Multi Language , Time Sync. : NTP, GMT, DST, Time Server, 15 Users (Admin., User1 ~ User14)</p> <p>, Video Recording: Speed: Max.15fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP) , AHD(720p,1080p,3MP, 4MP), CVI(720p, 1080p) , Analog SD(960H), HST - ET04 10 IP(Max. 4MP) , Bit Rate: 512Kbps ~ 3Mbps/Ch, Adjustable , Network Interface 1 X Ethernet 10/100/1G , H.264, USB, Network Interface , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED) , Output HDMI, VGA , RS485</p>		call us
11	HST-ET08	<p>8ch video , 8ch audio , 1 IPC (ONVIF Profile S) , 1 SATA OS : Embedded Linux - Built in flash memory, Multi Language, Time Sync. : NTP, GMT, DST, Time Server, 15 Users (Admin., User1 ~ User14)</p> <p>, Video Recording: Speed: Max.12fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP), AHD(720p,1080p,3MP, 4MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Bit Rate: 512Kbps ~ 3Mbps/Ch, Adjustable , Network Interface 1 X Ethernet 10/100/1G , H.264, USB, Network Interface , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED) , Output HDMI, VGA , RS485</p>		call us
12	HST-MT16	<p>16ch video, 16ch audio , 4 IPC (ONVIF Profile S) , 1 SATA OS : Embedded Linux - Built in flash memory, Multi Language, Time Sync. : NTP, GMT, DST, Time Server , 15 Users (Admin., User1 ~ User14)</p> <p>, Video Recording: Speed: Max.15fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP), AHD(720p,1080p,3MP, 4MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Bit Rate: 512Kbps ~ 3Mbps/Ch, Adjustable , Network Interface 1 X Ethernet 10/100/1G , H.264, USB, Network Interface , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , RS485</p>		call us

5brid (AHD/TVI/CVI/CVBS/IP) (4K) DVRs

13	HST-EH04	<p>4ch video , 4ch audio , 2 IPC (ONVIF Profile S) , 2 HDD or 1 HDD, 1 x eSATA OS : Embedded Linux, Multi Language, Time Sync. : NTP, GMT, DST, Time Server , 15 Users (Admin., User1 ~ User14) , Video Recording: Speed: Max.30fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Network Interface 2 X Ethernet 10/100/1G , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , 2 RS485 , RS232C</p>		call us
14	HST-MX08	<p>8ch video , 4ch audio , 4 IPC (ONVIF Profile S) , 2 HDD or 1 HDD, 1 x eSATA OS : Embedded Linux, Multi Language, Time Sync. : NTP, GMT, DST, Time Server , 15 Users (Admin., User1 ~ User14) , Video Recording: Speed: Max.30fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Network Interface 2 X Ethernet 10/100/1G , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , 2 RS485 , RS232C</p>		call us
15	HST-MX16	<p>16ch video , 8ch audio , 4 IPC (ONVIF Profile S) , 2 HDD or 1 HDD, 1 x eSATA OS : Embedded Linux, Multi Language, Time Sync. : NTP, GMT, DST, Time Server , 15 Users (Admin., User1 ~ User14) , Video Recording: Speed: Max.30fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Network Interface 2 X Ethernet 10/100/1G , Alarm 4 Input / 1 Output (E -mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , 2 RS485 , RS232C</p>		call us

16	HST-HD16	<p>16ch video, 16ch audio, 8 IPC(ONVIF Profile S) , 6 HDD, 2 eSATA OS: Embedded Linux, Multi Language, Time Sync.: NTP, GMT, DST, Time Server, 15 Users (Admin., User1 ~ User14) , Video Recording: Speed: Max.30fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Network Interface 2 X Ethernet 10/100/1G , Alarm 16 Input / 4 Output (E - mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , 2 RS485 , RS232C</p>		call us
17	HST-HD32	<p>32ch video, 16ch audio, 16 IPC (ONVIF Profile S) , 6 HDD, 2 eSATA OS: Embedded Linux, Multi Language, Time Sync.: NTP, GMT, DST, Time Server, 15 Users (Admin., User1 ~ User14) , Video Recording: Speed: Max.15fps/ch , Resolution: TVI(720p, 1080p, 3MP, 4MP, 5MP, 4K), AHD(720p,1080p, 3MP), CVI(720p, 1080p), Analog SD(960H), IP(Max. 4MP) , Network Interface 2 X Ethernet 10/100/1G , Alarm 16 Input /4 Output (E - mail, Event Popup, Buzzer, Relay, PTZ Preset, Remote VMS, Front LED), Output HDMI, VGA , 2 RS485 , RS232C</p>		call us